

MH200

Halogenfrei, dünnwandig 2:1

Halogen-Free, Thin Wall 2:1



Einsatzbereich

Überall dort, wo es im Brandfall nicht zu hohen Konzentrationen von ätzenden und giftigen Dämpfen kommen darf, wie in Schiffen, U-Booten, Flugzeugen und im schienengebundenen Personenverkehr.

Merkmale

Flexibler, halogenfreier Schrumpfschlauch Schrumpfverhältnis 2:1, Temperaturbereich -30° bis $+105^{\circ}\text{C}$, flammwidrig, DEF.STAN zugelassen. Farbe: schwarz (Standard)

*vor- bzw. nach Schrumpfvorgang

**Wandstärke bei freier Schrumpfung

Field of application

In all areas where concentrations of caustic and toxic fumes must not rise too highly in the event of fire, e.g. in ships, submarines, aeroplanes and in track-bound passenger transport.

Characteristics

Flexible, halogen-free heat-shrink tube, shrinkage ratio 2:1, Temperature range -30° to $+105^{\circ}\text{C}$, flame-resistant, DEF. STAN-approved. Colour: black (standard)

* before — after shrinking process

**Wall thickness in the case of variable shrinkage

Artikel-Nr. Article no.	Durchmesser Diameter mm *	Durchmesser Diameter inches	Wandstärke Wall thickness mm **	VPE Roll length m
MH200-32 -X	3,2-1,6	1/8	0,51	150
MH200-48 -X	4,8-2,4	3/16	0,51	75
MH200-64 -X	6,4-3,2	1/4	0,64	75
MH200-95 -X	9,5-4,8	3/8	0,64	75
MH200-127-X	12,7-6,4	1/2	0,64	50
MH200-190-X	19,0-9,5	3/4	0,76	50
MH200-254-X	25,4-12,7	1	0,89	30
MH200-380-X	38,0-19,0	1 1/2	1,02	30
MH200-508-X	50,8-25,4	2	1,14	15

Farben / Colorus:

					
Code:	0	4	5	6	9
	schwarz black	gelb yellow	grün green	blau blue	weiß white

Tel: +49 (0) 7361/9430-30

Fax: +49 (0) 7361/9430-32

MIL-KABEL-SYSTEMS GmbH • Am Nesselbach 25 • D-73434 Aalen • Germany • www.mil-kabel-systems.com